ENCLOSURE MODEL: LES 180-180-96 Job: ----WEBSITE: SAFE-T-COVER.COM EMAIL: SALES@SAFE-T-COVER.COM DRAWN BY: MTP SCALE: NONE DATE: 2/8/22 **ELEVATION VIEW** 18GA ALUMINUM ~ ROOF PANELS ARE REMOVABLE FOR MAINTENANCE 3" INSULATION ROOF (RI8) MINIMUM HEADER PANEL HEADER PANEL 7500 WATT OR WALL REMOVABLE ACCESS REMOVABLE ACCESS SWIVEL MOUNT HEATERS TWO THIS SIDE TWO THIS SIDE 96" INSIDE FAR SIDE 99 3/4" INSIDE NEAR SIDE TWO FAR SIDE TWO FAR SIDE ES 180-180-96 WALL 38½"W x 80"H 38<sup>1</sup>/<sub>4</sub>"W x 80"H DOOR HEIGHT INSULATION SHEET H\_9 194" CONCRETE PLAN VIEW 180" INSIDE 7,461 x -INSULATED HINGED DRAIN OPENING · , . · , · <u>, 4·</u> . ENCLOSURE INSIDE DIMENSIONS: 96" TALL INSIDE REMOVABLE ACCESS 96" TALL INSIDE REMOVABLE ACCESS 38½"W x 80"H 384"W x 80"H CONCRETE PAD IS 194"W MOUNTED MODEL LES 180-180-96 H.96 X 7.081 X M.08 48: SLOPING ROOF 94" CONCRETE Б. 9 INSIDE ~ INSULATION THICKNESS IS 3" MINIMUM. 80" WALL INSULATION THICKNESS IS I-I/2" TWO WALL OR CEILING MOUNTED HEATERS 7500 WATT - 208, 240 OR 480 VOLTS - AVAILABLE IN SINGLE PHASE OR THREE PHASE CONFIGURATIONS (WALL MOUNT ALLOWS SWIVEL ADJUSTMENT) ALL DIMENSIONS ARE IN INCHES. SCALE. 7500 WAT MOUNTED REMOVABLE ACCESS REMOVABLE ACCES 3/4" TALL INSIDE 38¼"W x 80"H 384"W x 80"H 99 3/4" TALL INSIDE DRAWING NOT INSULATED HINGED DRAIN OPENING-NOTE: ACCESS PANEL LOCATIONS CAN BE DETERMINED WHEN ENCLOSURE IS ORDERED THIS MODEL RECEIVES UP TO 6 ACCESS PANELS AT THE SAME PRICE. ROOF

CONFIDENTIAL: This drawing is intended for use only by those authorized to receive it.

Dissemination, distribution or copy of this information is strictly prohibited. US PATENT 5,609,784

- 22 25 -