SAFE-T-COV ENCLOSURE MODEL: 1000S-AL JOB: ----WEBSITE: SAFE-T-COVER.COM EMAIL: SALES@SAFE-T-COVER.COM DRAWN BY: MTP SCALE: NONE DATE: 11/30/22 **ELEVATION VIEW** 18GA ALUMINUM ~ ROOF PANELS ARE REMOVABLE FOR MAINTENANCE 3" INSULATION ROOF (RI8) REMOVABLE ACCESS REMOVABLE ACCESS 1000S-AL TWO THIS SIDE TWO THIS SIDE TWO FAR SIDE SHEET TWO FAR SIDE 38½"W x 78"H 38½"W x 78"H 78" INSIDE HCH2000-I20 ASSE 1060 CLASS I WET/DAMP CERTIFIED SLAB MOUNTED HEATER UNIT 40"W x 174"L x 78"H CONCRETE PAD IS 54"W X 188"L ENCLOSURE INSIDE DIMENSIONS: MODEL 1000S-AL ENCLOSURE PLAN VIEW 188" CONCRETE 5. 174" INSIDE 4.. REMOVABLE ACCESS REMOVABLE ACCESS 54" CONCRETE 38½"W x 78"H 38½"W x 78"H 40" INSIDE WALL INSULATION THICKNESS IS 1-1/2" ROOF INSULATION THICKNESS IS 3". HCH2000-I20 ALL DIMENSIONS ARE IN INCHES. REMOVABLE ACCESS REMOVABLE ACCESS 38½"W x 78"H 38½"W x 78"H

CONFIDENTIAL: THIS DRAWING IS INTENDED FOR USE ONLY BY THOSE AUTHORIZED TO RECEIVE IT. DISSEMINATION, DISTRIBUTION OR COPY OF THIS INFORMATION IS STRICTLY PROHIBITED. US PATENT 5,609,784 DRAWING NOT

- 2 m 4