ENCLOSURE MODEL: 800TDS-AL JOB: ----WEBSITE: SAFE-T-COVER.COM EMAIL: SALES@SAFE-T-COVER.COM DRAWN BY: MTP SCALE: NONE DATE: 2/21/22 **ELEVATION VIEW** 18GA ALUMINUM ~ ROOF PANELS ARE REMOVABLE FOR MAINTENANCE INSULATION ROOF (RI8) REMOVABLE ACCESS PANEL REMOVABLE ACCESS PANEL TWO THIS SIDE / TWO FAR SIDE TWO THIS SIDE / TWO FAR SIDE 38¼"W x 80"H 38¼"W x 80"H 800TDS-AL SHEET INSULATION WALL ( 80" INSIDE HCH2000-I20 MOUNTED HEATER HCH2000-120 <u>AB MOUNTED HEATER</u> CONCRETE PAD IS 92"W X 164"L X 6"H SLAB HEATERS ARE WET/DAMP CERTIFIED PER ASSE 1060 CLASS ENCLOSURE INSIDE DIMENSIONS: PLAN VIEW 78"W x I50"L x 80"H MODEL 800TDS-AL 164" CONCRETE 150" INSIDE 4.. REMOVABLE ACCESS WITH INSULATED HINGED DRAIN OPENING REMOVABLE ACCESS PANEL 5. 38¼"W x 80"H 38½"W x 80"H 92" CONCRETE 78" INSIDE HCH2000-I20

CONFIDENTIAL: This drawing is intended for use only by those authorized to receive it.

Dissemination, distribution or copy of this information is strictly prohibited. US PATENT 5,609,784

REMOVABLE ACCESS PANEL

38<sup>1</sup>/<sub>4</sub>"W x 80"H

REMOVABLE ACCESS WITH INSULATED HINGED DRAIN OPENING

38¼"W x 80"H

I. DRAWING NOT TO SCALE.

2. ALL DIMENSIONS ARE IN INCHES.

3. WALL INSULATION THICKNESS IS 1-1/2"

4. ROOF INSULATION THICKNESS IS 3".